

Hex Head Cap Screws

SAE Grade 8 J429 Zinc Phosphate & Oil



Coarse Thread. Alloy steel, quenched and tempered in accordance with SAE J429 material requirements and ANSI/ANSI B18.2.1 dimensional tolerances. Compatible with UNC and UNF grade 8 hex nuts, all metal lock nuts or nylon insert lock nuts. USS or SAE hardened flat washers as well as helical spring lock washers may also be used with these cap screws for a complete assembly.

1 1/4 - 7

Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
7 1/2"	1031359	310.00	1

1 1/2 - 6

Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
9"	1037417	539.40	1
10"	1037459	589.30	1

Hex Head Cap Screws

SAE Grade 8 J429 Zinc Black



Coarse Thread. Alloy steel, quenched and tempered in accordance with SAE J429 material requirements and ANSI/ANSI B18.2.1 dimensional tolerances. Compatible with UNC and UNF grade 8 hex nuts, all metal lock nuts or nylon insert lock nuts. USS or SAE hardened flat washers as well as helical spring lock washers may also be used with these cap screws for a complete assembly.

1/2 - 13

Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
2"	1011152	14.35	25

Reference numbers and part weights are provided as a reference only.
 Actual part weight may vary from weights shown.

Hex Head Cap Screws

SAE Grade 8 J429 Magni 565 Gray



Alloy steel, quenched and tempered in accordance with SAE J429 material requirements and ANSI/ANSI B18.2.1 dimensional tolerances. Compatible with UNC and UNF grade 8 hex nuts, all metal lock nuts or nylon insert lock nuts. USS or SAE hardened flat washers as well as helical spring lock washers may also be used with these cap screws for a complete assembly.

Coarse Thread			
3/8 - 16			
Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
3/4"	1998192	3.55	100
1 1/4"	2005683	4.86	50
1 1/2"	1998190	5.64	50

1/2 - 13			
Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
1"	1998188	9.22	25
1 1/4"	1998187	10.34	25
1 1/2"	1994433	11.59	25
2 3/4"	1998182	18.49	10
6"	1998180	36.43	10

5/8 - 11			
Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
2 1/2"	1058611	27.13	10

3/4 - 10			
Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
4 1/2"	2006876	66.22	5

Fine Thread			
1/2 - 20			
Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
3/4"	1994082	8.10	50

5/8 - 18			
Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
2 1/4"	1998179	24.97	10

1 - 14			
Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
3"	2006255	90.96	1

Hex Head Cap Screws

SAE Grade 8 J429 Zinc Clear



Alloy steel, quenched and tempered in accordance with SAE J429 material requirements and ANSI/ANSI B18.2.1 dimensional tolerances. Compatible with UNC and UNF grade 8 hex nuts, all metal lock nuts or nylon insert lock nuts. USS or SAE hardened flat washers as well as helical spring lock washers may also be used with these cap screws for a complete assembly.

Coarse Thread			
3/4 - 10			
Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
2 1/4"	1019147	38.23	10

7/8 - 9			
Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
4 1/4"	1022227	88.98	1

Fine Thread			
1/2 - 20			
Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
2 1/4"	1012143	15.73	10

7/8 - 14			
Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
5 1/4"	1023267	107.76	20

Reference numbers and part weights are provided as a reference only. Actual part weight may vary from weights shown.

Hex Head Cap Screws

SAE Grade 8 J429 Zinc Trivalent Clear with Sealer



Coarse Thread Alloy steel, quenched and tempered in accordance with SAE J429 material requirements and ANSI/ANSI B18.2.1 dimensional tolerances. Compatible with UNC and UNF grade 8 hex nuts, all metal lock nuts or nylon insert lock nuts. USS or SAE hardened flat washers as well as helical spring lock washers may also be used with these cap screws for a complete assembly.

1/4 - 20

Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
3/4"	2014550	1.44	100

SAE Grade 8 J429

Hex Head Cap Screws

GM6035M Zinc Phosphate and Oil



Coarse Thread Alloy steel, quenched and tempered in accordance with SAE J429 material requirements and ANSI/ANSI B18.2.1 dimensional tolerances. Compatible with UNC and UNF grade 8 hex nuts, all metal lock nuts or nylon insert lock nuts. USS or SAE hardened flat washers as well as helical spring lock washers may also be used with these cap screws for a complete assembly.

1 - 8

Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
9 1/4"	1811372	229.02	1
10"	1811375	245.60	1

Hex Head Cap Screws

SAE Grade 5 J429 Magni 565 Gray




Fine Thread Alloy steel, quenched and tempered in accordance with SAE J429 material requirements and ANSI/ANSI B18.2.1 dimensional tolerances. Compatible with UNC and UNF grade 8 hex nuts, all metal lock nuts or nylon insert lock nuts. USS or SAE hardened flat washers as well as helical spring lock washers may also be used with these cap screws for a complete assembly.

1 - 14

Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity
6"	1994081	157.20	1

Hex Head Cap Screws

SAE Grade 8 J429 Copper Plate (.0005 to .0008 thick)



Coarse Thread. Copper plated to .0004 - .0008 thickness. Alloy steel, quenched and tempered in accordance with SAE J429 material requirements and ANSI/ANSI B18.2.1 dimensional tolerances. Compatible with UNC and UNF grade 8 hex nuts, all metal lock nuts or nylon insert lock nuts. USS or SAE hardened flat washers as well as helical spring lock washers may also be used with these cap screws for a complete assembly.

3/8 - 16

Length	Part Number	Lbs. Per 100 Pcs.	Package Quantity	Reference Part No.
1 3/8"	1006087	5.25	50	405537R1

See
Grade 5
on
Page
38.

Reference numbers and part weights are provided as a reference only. Actual part weight may vary from weights shown.

1-888-232-1010
 fax: (563) 441-6760

www.TrinityHardwareHQ.com
sales@TrinityHardwareHQ.com